




BR-12.5M 4P

T1+T2 Surge Arrester



■ BR-12.5M 4P is suitable for TN-S system.

		BR-12.5M 150 4P	BR-12.5M 275 4P	BR-12.5M 320 4P
SPD classification according to EN61643-11		Type 1 + Type 2	Type 1 + Type 2	Type 1 + Type 2
SPD classification according to IEC61643-11		Class I + Class II	Class I + Class II	Class I + Class II
Max. continuous operating a.c. voltage	Uc	150V	275V	320V
Lightning impulse current (10/350μs)	Iimp	12.5kA	12.5kA	12.5kA
Total discharge current (10/350μs)	Itotal	50kA	50kA	50kA
Nominal discharge current (8/20μs)	In	25kA	25kA	25kA
Max. discharge current (8/20μs)	Imax	60kA	60kA	60kA
Voltage protection level	Up	≤0.8kV	≤1.3kV	≤1.5kV
Specific energy	W/R	39kJ/Ω	39kJ/Ω	39kJ/Ω
Short circuit withstand capacity	IscCR	25kA	25kA	25kA
Temporary overvoltage TOV-withstand	UT	180V/5sec.	335V/5sec.	400V/5sec.
Temporary overvoltage TOV-safe failure	UT	230V/120min.	440V/120min.	520V/120min.
Max. backup fuse		125A gG	125A gG	125A gG
Leakage current	IPE	<0.5mA	<0.5mA	<0.5mA
Response time	tA	≤25ns	≤25ns	≤25ns
Operating temperature range	Tu	-40°C–80°C	-40°C–80°C	-40°C–80°C
Operating state/fault indication		green/red	green/red	green/red
Cross-section area (Min.)		4mm ²	4mm ²	4mm ²
Cross-section area (Max.)		35mm ²	35mm ²	35mm ²
For mounting on		35mm Din rail		
Enclosure material		Thermoplastic UL94-V0		
Degree of protection		IP20	IP20	IP20
Order Code		B18411	B18413	B18415
Order Code (With remote signaling)		B18412	B18414	B18416